

SEALANT (IF REQUIRED FOR THE SPECIFIC SYSTEM)

1/2" [13 mm] MIN. CLEARANCE

2" [50 mm] MIN. CLEARANCE

1 1/2" [38mm] MIN. FOR BALLASTED SYSTEMS

FLANGE APPROX. 3" [75 mm] WIDE

APPROX. 3" [75 mm]

1" [25mm] MIN. BELOW BLOCKING

ADHERED FLASHING MEMBRANE (EXTEND APPROX. 3" [75 mm] BEYOND FLANGE)

FASTENERS 3" to 6" [75 to 150 mm] O.C.; STAGGER

SHEET METAL "GRAVEL STOP" (AS REQUIRED BY MANUFACTURER)

THERMOSET ROOF MEMBRANE

COVERBOARD AND THERMAL INSULATION

ROOF DECK

WOOD NAILERS

EXTEND FIELD SHEET TO BELOW BLOCKING

CONTINUOUS CLEAT (FASTENED PER SINGLE-PLY TABLE 1)

NOTES :

1. NRCA SUGGESTS AVOIDING (WHERE POSSIBLE) FLASHING DETAILS THAT REQUIRE RIGID METAL FLANGES TO BE EMBEDDED OR SANDWICHED INTO THE ROOF MEMBRANE.
2. THIS DETAIL SHOULD BE USED ONLY WHERE THE DECK IS SUPPORTED BY THE OUTSIDE WALL.
3. REFER TO THE SHEET METAL SECTION OF THE METAL ROOFING MANUAL FOR JOINERY AND SECUREMENT OPTIONS FOR SHEET METAL.
4. REFER TO THE INTRODUCTION FOR ADDITIONAL INFORMATION.



**EMBEDDED EDGE METAL FLASHING (GRAVEL-STOP)**

2001

NOT DRAWN TO SCALE

**TS-3**